IMPARTE
EQUIPAMENTOS DE SEGURANÇA

EXFAEX ANEPC Registo 271

Technical Data Sheet

Designation PORTABLE ABC DRY POWDER EXTINGUISHER, MARINE, 3KG AND 6KG

Brand EXFAEX **Ref. No.** EX13; EX16

General Description

This portable ABC dry powder fire extinguisher, designed for marine environments, is lightweight and certified for use in areas exposed to high salinity and humidity.

It is suitable for installation on pleasure craft, merchant navy vessels and port infrastructure where firefighting equipment is exposed to aggressive environmental conditions.

The dry powder extinguishing agent provides proven effectiveness against class A (combustible solids), B (flammable liquids) and C (flammable gases) fires. Its low dispersion allows the jet to be directed precisely, optimising flame suppression and reducing interference with the operator's visibility.

The powder used is non-corrosive, non-abrasive and non-toxic to humans and animals, ensuring operational safety and minimising the risk of damage to sensitive equipment.

Features

- High-quality steel cylinder with anti-corrosion treatment that ensures tightness;
- Brass valve, ensuring opening without breaking during use, recharging or hydrostatic testing;
- Self-checking pressure gauge;
- Lead- and TGIC-free polyester paint, resistant to ultraviolet radiation;
- Flexible rubber hose covered in black polyamide, with tubular nozzle (Ref. EX16 only);

Standards, certificates, marking and documentation

- CE marking in accordance with NP671-2:2013;
- Standard UNE-EN 3-7:2004/A1:2008 and UNE-EN 3-10:2010;

Additional Products

- Photoluminescent signage in accordance with 92/58/EEC not included;
- Stainless steel bracket with rubber strap not included;
- Protective cover not included;

How to order

- Ref. EX13_ABC dry powder extinguisher 3kg marine-Exfaex;
- Ref. EX16_ABC dry powder extinguisher 6kg marine-Exfaex.



- Ref. EXC12;
- Effectiveness: 34A-233 B-C;
- Extinguishing agent: ABC powder (6kg);
- Propellant: N2;
- Max. height: 528mm;
- Diameter: 150mm;
- Weight: 9.22kg;
- Operating temp.: -20°/+60°;
- Test pressure: 23bar;
- Dielectric test: 1000V.



- Ref. EX13;
- Effectiveness: 13A-89 B-C;
- Extinguishing agent: ABC powder (3kg);
- Propellant: N2;
- Max. height: 470mm;
- Diameter: 110mm;
- Weight: 5.15kg;
- Operating temp.: -20°/+60°;
- Test pressure: 23bar;
- Dielectric test: 1000V.

As an innovative company, IMPARTE S.A. reserves the right to change product specifications, models and standard equipment without prior notice and without incurring any obligation.
For more information visit www.imparte.pt or contact our sales department.

The illustrative images show the product(s) presented; however, they may differ slightly from the final product(s).

www.imparte.pt

HQ| Edifício Imparte, Alto da Barrada,
2785-646 São Domingos de Rana, Portugal

(+351) 214 448 440
(Call to a national landline)

geral@imparte.pt