IMPARTE
EQUIPAMENTOS DE SEGURANÇA

Technical Data Sheet

Designation WHEELED ABC DRY POWDER EXTINGUISHER, 25KG, 50KG AND 100KG

Brand EXFAEX **Ref. No.** EX21; EX22; EX23

General Description

The ABC dry powder extinguisher is firefighting equipment designed for versatile, efficient use. It is supplied on a sturdy transport trolley built from resistant metal tube, fitted with plastic and rubber wheels for easy mobility. The structure has an epoxy paint finish for greater durability and corrosion protection.

The dry powder used is suitable for the following fire classes:

- Class A — combustible solids, such as wood, paper or fabrics.
- Class B — flammable liquids, such as fuels and solvents.
- Class C — flammable gases.
- The powder used is non-corrosive, non-abrasive and non-toxic to humans and animals, ensuring operational safety and minimising the risk of damage to sensitive equipment.

Features

- High-quality steel cylinder with anti-corrosion treatment that ensures tightness;
- Quick-discharge valve with internal pressure check device;
- Self-checking pressure gauge;
- Lead- and TGIC-free polyester paint, resistant to ultraviolet radiation;
- Flexible rubber hose with tubular nozzle;
- Transport trolley built from resistant metal tube with plastic and rubber wheels, painted in RAL 3000 “Red” epoxy, included;

Standards, certificates, marking and documentation

- CE marking in accordance with NP671-2:2013;
- Standard UNE-EN 3-7:2004/A1:2008 and UNE-EN 3-10:2010;

Additional Products

- Photoluminescent signage in accordance with 92/58/EEC not included;
- Protective cover not included;

How to order

- Ref. EX21_dry powder extinguisher 25kg with trolley-Exfaex;
- Ref. EX22_dry powder extinguisher 50kg with trolley-Exfaex;
- Ref. EX23_dry powder extinguisher 100kg with trolley-Exfaex;



Ref. EX21;	Ref. EX23;	Ref. EX22;
Effectiveness: A – B - C;	Effectiveness: A – B - C;	Effectiveness: A – B - C;
Extinguishing agent:	Extinguishing agent:	Extinguishing agent:
ABC powder (25kg);	ABC powder (100kg);	ABC powder (50kg);
Propellant: N2;	Propellant: N2;	Propellant: N2;
Max. height: 915mm;	Max. height: 985mm;	Max. height: 915mm;
Diameter: 250mm;	Diameter: 400mm;	Diameter: 300mm;
Weight: 42.50kg;	Weight: 140.50kg;	Weight: 74kg;
Operating temp.:-20°/+60°;	Operating temp.:-20°/+60°;	Operating temp.:-20°/+60°;
Test pressure: 23bar.	Test pressure: 23bar.	Test pressure: 23bar.

As an innovative company, IMPARTE S.A. reserves the right to change product specifications, models and standard equipment without prior notice and without incurring any obligation.
For more information visit www.imparte.pt or contact our sales department.

The illustrative images show the product(s) presented; however, they may differ slightly from the final product(s).

www.imparte.pt

HQ| Edifício Imparte, Alto da Barrada,
2785-646 São Domingos de Rana, Portugal

(+351) 214 448 440
(Call to a national landline)

geral@imparte.pt