IMPARTE
EQUIPAMENTOS DE SEGURANÇA

Technical Data Sheet

Designation 10 AND 20 KG WHEELED CO2 FIRE EXTINGUISHER

Brand EXFAEX **Ref. No.** EXC13; EXC14

General Description

Mobile fire extinguisher permanently pressurised with CO2 (carbon dioxide), in a one-piece alloy steel cylinder. Rechargeable extinguisher.

10 kg CO2 extinguishers are transportable extinguishers mounted on a trolley made of 1" steel tube with two wheels and solid tyres whose size varies according to the weight to be moved.

CO2 extinguishers are recommended for fighting class B and C fires and fires with no defined fire class involving electrical and electronic equipment, as CO2 does not conduct electricity; they are also suitable for extinguishing fires caused by the combustion of flammable liquids (oil, petrol, alcohol, paint, waxes, varnishes, etc.) or flammable gases (natural gas, butane, propane, acetylene, ethylene, etc.).

Using CO2 extinguishers leaves no residue and does not damage equipment.

Features

- Anti-corrosion internal coating;
- Long-range spray diffuser;
- Manual valve or lever;
- Self-checking pressure gauge;
- Seamless rolled steel cylinder;
- Lead- and TGIC-free polyester paint, resistant to ultraviolet radiation;
- Flexible rubber hose covered in black polyamide, with tubular nozzle;
- Transport trolley made of 1" steel tube with two wheels included;

Standards, certificates, marking and documentation

- CE marking – No.: A21/000070 Aenor;

Additional Products

- Photoluminescent signage in accordance with 92/58/EEC not included;
- Protective cover not included;

How to order

- Ref. EXC13_CO2 extinguisher 10kg with trolley-Exfaex;
- Ref. EXC14_CO2 extinguisher 20kg with trolley-Exfaex.



- Ref. EXC13;
- Extinguishing agent: CO2;
- Nominal charge: 9.5 to 10kg CO2;
- Max. height: 963mm;
- Diameter: 154mm;
- Extinguisher weight: 29kg;
- Weight with trolley: 30.625kg
- Operating temp.: -20°/+60°;
- Test pressure: 250bar;
- Max. working pressure: 174bar;
- Cylinder burst pressure: 510bar.



- Ref. EXC14;
- Extinguishing agent: CO2;
- Nominal charge: 9.5 to 10kg CO2;
- Max. height: 963mm;
- Diameter: 154mm;
- Extinguisher weight: 23.75kg x2 (2 units per trolley);
- Weight with trolley: 59.285kg
- Operating temp.: -20°/+60°;
- Test pressure: 250bar;
- Max. working pressure: 174bar;
- Cylinder burst pressure: 510bar.

As an innovative company, IMPARTE S.A. reserves the right to change product specifications, models and standard equipment without prior notice and without incurring any obligation.
For more information visit www.imparte.pt or contact our sales department.

The illustrative images show the product(s) presented; however, they may differ slightly from the final product(s).

www.imparte.pt

HQ| Edifício Imparte, Alto da Barrada,
2785-646 São Domingos de Rana, Portugal

(+351) 214 448 440
(Call to a national landline)

geral@imparte.pt