IMPARTE
EQUIPAMENTOS DE SEGURANÇA

Technical Data Sheet

Designation FLAT HOSE, Ø25, 45, 50 AND 70, LENGTHS 20, 25 AND 100M

Brand HELI **Ref. No.** MG25.06 TO MG[x]



Features

The fire hose is designed to help fight fires and save lives and property, so this equipment is intrinsically linked to good quality and performance. It is always worth stressing that fire hoses are not a single product: there are different models, each with specific characteristics and applications that vary according to diameter, pressure, manufacture and type of use.

To help you choose the right fire hose, count on Imparte S.A. Contact us for technical support and a free quote.

Inspecting and maintaining a fire hose is as important as choosing it, so that safety and good performance are maintained.

Construction features

- Double-layer flat hose in flexible PVC reinforced with polyester textile mesh, smooth bore, black;
- Abrasion resistance;
- Robust at high pressures;
- Flexible and easy to handle;
- Working pressure 12 to 15bar;
- Burst pressure 36 to 48bar;
- Operating temperature -10 to +55°C;

Application

- Public and Industrial Buildings;
- Construction;
- Agriculture;

Standards, certificates, marking and documentation

- CE marking in accordance with NP671-2:2013;
- In accordance with NP EN 694:2014;
- Certified product;

Optional and/or additional

- Photoluminescent signage in accordance with 92/58/EEC;

How to order

- Ref. MG25.05__Flat hose 25mm black, 25m;
- Ref. MG25.06__Flat hose 25mm black, 100m;
- Ref. MG25.102_Flat hose 25mm black, 25m, with Storz couplings;
- Ref. MG25.103_Flat hose 25mm black, 25m, with Storz couplings;
- Other sizes available.

The images shown are for illustration only and may differ slightly from the final product(s).

www.imparte.pt

HQ| Edifício Imparte, Alto da Barrada,
2785-646 São Domingos de Rana, Portugal

(+351) 214 448 440
(Call to a national landline)

geral@imparte.pt